

# ULTIMATE S U P P O R T™

THE STRENGTH OF INNOVATION

## LIVE MIC STAND

The perfect performer stands for 20 years...innovation, reinvented.

Ergo, one-handed clutch holds better than any other one-handed stand. Give your mic attitude. Ask about our optional custom mic tops.



STANDARD HEIGHT / WEIGHTED BASE

Rev. 1 03.16.09 . Hang Tag Item #17205T





## FEATURES OF LIVE-ST

**New And Improved “Ergo” Clutch** - The new ergonomic handle feels great in your hand and is so easy to use.

**Patented Universal Mic Attachment** - Top threads fit both US- and metric-threaded mic clips and accessories.

**Aluminum Construction** - Durable, anodized aluminum construction creates a strong, ultra lightweight stand preferred by lead singers.

**Sturdy Weighted Base** - If you prefer some weight, select a strong, die-cast weighted base in two stable options: standard or stackable. Stackable base cut-out allows up to six stands to stack in the footprint of one for convenient storage and transport.

**Customizable** - Retro fit any of the NEW Custom Mic Tops onto any of the Live Series stands with full functionality for your own unique style.

**Limited Lifetime Warranty** - This product is constructed of the finest materials and backed by our award-winning customer support. For full details, exclusions, and limitations, as well as information on obtaining warranty service, visit [www.ultimatesupport.com](http://www.ultimatesupport.com).

---

## INSTRUCTIONS FOR SETTING UP THE STAND

1. Screw shaft into weighted base. Live Series shafts and weighted bases are interchangeable.
2. While squeezing the trigger, raise or lower the clutch/upper shaft to your desired height. Release the trigger and the internal lock engages for a secure and reliable hold.
3. Choose US or metric mic attachment and place mic on stand, then turn MIC-Lock.

*Visit [www.ultimatesupport.com](http://www.ultimatesupport.com) to download a detailed product manual, read full warranty details and to register your warranty.*

## SPECS OF LIVE-ST

- Item #17205—black
- Height 44.5” - 74”  
(1130 mm - 1880 mm)
- Tube diameter 1” (25 mm)